

824 Application Advice

Functional Group ID=**AG**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Application Advice Transaction Set (824) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide the ability to report the results of an application system's data content edits of transaction sets. The results of editing transaction sets can be reported at the functional group and transaction set level, in either coded or free-form format. It is designed to accommodate the business need of reporting the acceptance, rejection or acceptance with change of any transaction set. The Application Advice should not be used in place of a transaction set designed as a specific response to another transaction set (e.g., purchase order acknowledgment sent in response to a purchase order).

Notes:

- 1. Used by the processing activity for functional reject of select transactions.*
- 2. This transaction set is not used to reject a transmission due to ASC X12 syntax errors. Use a 997 transaction set for that purpose.*
- 3. DoD logistics users should refer to the Defense Logistics Management System (DLMS) Supplement to the Federal Implementation Convention (IC) available at URL: <http://www.dla.mil/j-6/dlms>. The DLMS Supplement provides specific business rules, conditions, and authorized codes necessary for appropriate use of this IC within the DLMS.*

Heading:

Page No.	Pos. No.	Seg. ID	Name	Req. Des.	Max.Use	Loop Repeat	Notes and Comments
3	010	ST	Transaction Set Header	M	1		
4	020	BGN	Beginning Segment	M	1		
LOOP ID - N1						>1	
6	030	N1	Name	O	1		
Not Used	040	N2	Additional Name Information	O	2		
Not Used	050	N3	Address Information	O	2		
Not Used	060	N4	Geographic Location	O	1		
Not Used	070	REF	Reference Identification	O	12		
7	080	PER	Administrative Communications Contact	O	3		

Detail:

Page No.	Pos. No.	Seg. ID	Name	Req. Des.	Max.Use	Loop Repeat	Notes and Comments
LOOP ID - OTI						>1	

9	010	OTI	Original Transaction Identification	M	1	n1
12	020	REF	Reference Identification	O	12	n2
14	030	DTM	Date/Time Reference	O	2	n3
Not Used	040	PER	Administrative Communications Contact	O	3	n4
Not Used	050	AMT	Monetary Amount	O	>1	n5
Not Used	060	QTY	Quantity	O	>1	n6
15	065	NM1	Individual or Organizational Name	O	9	n7
LOOP ID - TED					>1	
17	070	TED	Technical Error Description	O	1	
Not Used	080	NTE	Note/Special Instruction	O	100	
Not Used	082	RED	Related Data	O	100	n8
LOOP ID - LM					>1	
18	085	LM	Code Source Information	O	1	n9
LOOP ID - LQ					100	
19	086	LQ	Industry Code	M	1	
Not Used	087	RED	Related Data	O	100	n10
20	090	SE	Transaction Set Trailer	M	1	

Transaction Set Notes

1. The OTI loop is intended to provide a unique identification of the transaction set that is the subject of this application acknowledgment.
2. The REF segment allows for the provision of secondary reference identification or numbers required to uniquely identify the original transaction set. The primary reference identification or number should be provided in elements OTI02-03.
3. The DTM segment allows for the provision of date, time, or date and time information required to uniquely identify the original transaction set.
4. The PER segment should be utilized if administrative communications contact information is important to the unique identification of the original transaction set.
5. The AMT segment should be utilized if monetary amount information is important to the unique identification of the original transaction set.
6. The QTY segment should be utilized if quantity information is important to the unique identification of the original transaction set.
7. The NM1 segment allows for the provision of entity identification information required to uniquely identify the original transaction set.
8. The RED segment may be used to provide data related to the error condition specified in the associated TED01 element.
9. The LM loop is used to identify industry-based or proprietary application error conditions.
10. The RED segment may be used to provide data related to the error condition specified in the associated LQ02 element.

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
Comments:

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	ST01	143	Transaction Set Identifier Code	M ID 3/3
			Code uniquely identifying a Transaction Set	
			824 Application Advice	
M	ST02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	
			<i>Use to identify a unique number assigned by the originator of the transaction set. This number may be system generated.</i>	

Segment: **BGN** Beginning Segment
Position: 020
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of a transaction set
Syntax Notes: 1 If BGN05 is present, then BGN04 is required.
Semantic Notes: 1 BGN02 is the transaction set reference number.
2 BGN03 is the transaction set date.
3 BGN04 is the transaction set time.
4 BGN05 is the transaction set time qualifier.
5 BGN06 is the transaction set reference number of a previously sent transaction affected by the current transaction.
Comments:

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	BGN01	353	Transaction Set Purpose Code Code identifying purpose of transaction set 00 Original 77 Simulation Exercise	M ID 2/2
M	BGN02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M AN 1/30
M	BGN03	373	Date Date expressed as CCYYMMDD	M DT 8/8
Not Used	BGN04	337	Time Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	X TM 4/8
Not Used	BGN05	623	Time Code Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow	O ID 2/2
Not Used	BGN06	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	O AN 1/30
	BGN07	640	Transaction Type Code	O ID 2/2

			Code specifying the type of transaction	
			ZT	Report of Rejection or Return of Work Candidate
Not Used	BGN08	306	Action Code	O ID 1/2
			Code indicating type of action	
Not Used	BGN09	786	Security Level Code	O ID 2/2
			Code indicating the level of confidentiality assigned by the sender to the information following	

Segment:	N1 Name
Position:	030
Loop:	N1 Optional
Level:	Heading
Usage:	Optional
Max Use:	1
Purpose:	To identify a party by type of organization, name, and code
Syntax Notes:	<ol style="list-style-type: none"> 1 At least one of N102 or N103 is required. 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:	
Comments:	<ol style="list-style-type: none"> 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party. 2 N105 and N106 further define the type of entity in N101.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	N101	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual <i>Use any code.</i> Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/3
Not Used	N102	93	Name Free-form name	X AN 1/60
	N103	66	Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67) <ol style="list-style-type: none"> 1 D-U-N-S Number, Dun & Bradstreet 9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix 10 Department of Defense Activity Address Code (DODAAC) M4 Department of Defense Routing Identifier Code (RIC) 	X ID 1/2
	N104	67	Identification Code Code identifying a party or other code	X AN 2/80
Not Used	N105	706	Entity Relationship Code Code describing entity relationship	O ID 2/2
Not Used	N106	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual	O ID 2/3

Segment: **PER** **Administrative Communications Contact**
Position: 080
Loop: N1 Optional
Level: Heading
Usage: Optional
Max Use: 3
Purpose: To identify a person or office to whom administrative communications should be directed

Syntax Notes:

- 1 If either PER03 or PER04 is present, then the other is required.
- 2 If either PER05 or PER06 is present, then the other is required.
- 3 If either PER07 or PER08 is present, then the other is required.

Semantic Notes:
Comments:

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	PER01	366	Contact Function Code	M ID 2/2
			Code identifying the major duty or responsibility of the person or group named	
			IC Information Contact	
	PER02	93	Name	O AN 1/60
			Free-form name	
	PER03	365	Communication Number Qualifier	X ID 2/2
			Code identifying the type of communication number	
			AU Defense Switched Network	
			EM Electronic Mail	
			FX Facsimile	
			TE Telephone	
			WF Work Facsimile Number	
	PER04	364	Communication Number	X AN 1/80
			Complete communications number including country or area code when applicable	
	PER05	365	Communication Number Qualifier	X ID 2/2
			Code identifying the type of communication number	
			AU Defense Switched Network	
			EM Electronic Mail	
			FX Facsimile	
			TE Telephone	
			WF Work Facsimile Number	
	PER06	364	Communication Number	X AN 1/80
			Complete communications number including country or area code when	

		applicable	
PER07	365	Communication Number Qualifier	X ID 2/2
		Code identifying the type of communication number	
		AU Defense Switched Network	
		EM Electronic Mail	
		FX Facsimile	
		TE Telephone	
		WF Work Facsimile Number	
PER08	364	Communication Number	X AN 1/80
		Complete communications number including country or area code when applicable	
PER09	443	Contact Inquiry Reference	O AN 1/20
		Additional reference number or description to clarify a contact number	

Segment:	OTI Original Transaction Identification
Position:	010
Loop:	OTI Mandatory
Level:	Detail
Usage:	Mandatory
Max Use:	1
Purpose:	To identify the edited transaction set and the level at which the results of the edit are reported, and to indicate the accepted, rejected, or accepted-with-change edit result
Syntax Notes:	1 If OTI09 is present, then OTI08 is required.
Semantic Notes:	1 OTI03 is the primary reference identification or number used to uniquely identify the original transaction set. 2 OTI06 is the group date. 3 OTI07 is the group time. 4 If OTI11 is present, it will contain the version/release under which the original electronic transaction was translated by the receiver. 5 OTI12 is the purpose of the original transaction set, and is used to assist in its unique identification. 6 OTI13 is the type of the original transaction set, and is used to assist in its unique identification. 7 OTI14 is the application type of the original transaction set, and is used to assist in its unique identification. 8 OTI15 is the type of action indicated or requested by the original transaction set, and is used to assist in its unique identification. 9 OTI16 is the action requested by the original transaction set, and is used to assist in its unique identification. 10 OTI17 is the status reason of the original transaction set, and is used to assist in its unique identification.
Comments:	1 OTI02 contains the qualifier identifying the business transaction from the original business application, and OTI03 will contain the original business application identification. 2 If used, OTI04 through OTI08 will contain values from the original electronic functional group generated by the sender. 3 If used, OTI09 through OTI10 will contain values from the original electronic transaction set generated by the sender.

Data Element Summary

Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	OTI01	110 Application Acknowledgment Code	M ID 1/2
		Code indicating the application system edit results of the business data	
		<i>Use any code.</i>	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
M	OTI02	128 Reference Identification Qualifier	M ID 2/3
		Code qualifying the Reference Identification	
		<i>Use any code.</i>	

			Refer to 004010 Data Element Dictionary for acceptable code values.	
M	OTI03	127	Reference Identification	M AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	
Not Used	OTI04	142	Application Sender's Code	O AN 2/15
			Code identifying party sending transmission; codes agreed to by trading partners	
Not Used	OTI05	124	Application Receiver's Code	O AN 2/15
			Code identifying party receiving transmission; codes agreed to by trading partners	
Not Used	OTI06	373	Date	O DT 8/8
			Date expressed as CCYYMMDD	
Not Used	OTI07	337	Time	O TM 4/8
			Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	
	OTI08	28	Group Control Number	X N0 1/9
			Assigned number originated and maintained by the sender	
	OTI09	329	Transaction Set Control Number	O AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	
	OTI10	143	Transaction Set Identifier Code	O ID 3/3
			Code uniquely identifying a Transaction Set	
			Refer to 004010 Data Element Dictionary for acceptable code values.	
	OTI11	480	Version / Release / Industry Identifier Code	O AN 1/12
			Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed	
			Refer to 004010 Data Element Dictionary for acceptable code values.	
	OTI12	353	Transaction Set Purpose Code	O ID 2/2
			Code identifying purpose of transaction set	
			Refer to 004010 Data Element Dictionary for acceptable code values.	
	OTI13	640	Transaction Type Code	O ID 2/2
			Code specifying the type of transaction	
			Refer to 004010 Data Element Dictionary for acceptable code values.	
Not Used	OTI14	346	Application Type	O ID 2/2
			Code identifying an application	

	OTI15	306	Action Code	O ID 1/2
			Code indicating type of action	
			Refer to 004010 Data Element Dictionary for acceptable code values.	
Not Used	OTI16	305	Transaction Handling Code	O ID 1/2
			Code designating the action to be taken by all parties	
	OTI17	641	Status Reason Code	O ID 3/3
			Code indicating the status reason	
			Refer to 004010 Data Element Dictionary for acceptable code values.	

Segment:	REF Reference Identification
Position:	020
Loop:	OTI Mandatory
Level:	Detail
Usage:	Optional
Max Use:	12
Purpose:	To specify identifying information
Syntax Notes:	<ol style="list-style-type: none"> 1 At least one of REF02 or REF03 is required. 2 If either C04003 or C04004 is present, then the other is required. 3 If either C04005 or C04006 is present, then the other is required.
Semantic Notes:	<ol style="list-style-type: none"> 1 REF04 contains data relating to the value cited in REF02.
Comments:	

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification <i>Use any code.</i> Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/3
	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X AN 1/30
	REF03	352	Description A free-form description to clarify the related data elements and their content	X AN 1/80
	REF04	C040	Reference Identifier To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier	O
M	C04001	128	Reference Identification Qualifier Code qualifying the Reference Identification <i>Use any code.</i> Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/3
	C04002	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M AN 1/30
M	C04003	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004010 Data Element Dictionary for acceptable code values.	X ID 2/3
	C04004	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X AN 1/30

C04005	128	Reference Identification Qualifier	X	ID 2/3
		Code qualifying the Reference Identification		
		Refer to 004010 Data Element Dictionary for acceptable code values.		
C04006	127	Reference Identification	X	AN 1/30
		Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier		

Segment: DTM Date/Time Reference**Position:** 030**Loop:** OTI Mandatory**Level:** Detail**Usage:** Optional**Max Use:** 2**Purpose:** To specify pertinent dates and times

- Syntax Notes:**
- 1 At least one of DTM02 DTM03 or DTM05 is required.
 - 2 If DTM04 is present, then DTM03 is required.
 - 3 If either DTM05 or DTM06 is present, then the other is required.

Semantic Notes:**Comments:****Data Element Summary**

	<u>Ref.</u>	<u>Data</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	DTM01	374		Date/Time Qualifier	M ID 3/3
				Code specifying type of date or time, or both date and time	
				<i>Use any code.</i>	
				Refer to 004010 Data Element Dictionary for acceptable code values.	
	DTM02	373		Date	X DT 8/8
				Date expressed as CCYYMMDD	
	DTM03	337		Time	X TM 4/8
				Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	
Not Used	DTM04	623		Time Code	O ID 2/2
				Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow	
Not Used	DTM05	1250		Date Time Period Format Qualifier	X ID 2/3
				Code indicating the date format, time format, or date and time format	
Not Used	DTM06	1251		Date Time Period	X AN 1/35
				Expression of a date, a time, or range of dates, times or dates and times	

Segment: **NM1** **Individual or Organizational Name**
Position: 065
Loop: OTI Mandatory
Level: Detail
Usage: Optional
Max Use: 9
Purpose: To supply the full name of an individual or organizational entity
Syntax Notes: 1 If either NM108 or NM109 is present, then the other is required.
2 If NM111 is present, then NM110 is required.
Semantic Notes: 1 NM102 qualifies NM103.
Comments: 1 NM110 and NM111 further define the type of entity in NM101.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	NM101	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual <i>Use any code.</i> Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/3
M	NM102	1065	Entity Type Qualifier Code qualifying the type of entity Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 1/1
Not Used	NM103	1035	Name Last or Organization Name Individual last name or organizational name	O AN 1/35
Not Used	NM104	1036	Name First Individual first name	O AN 1/25
Not Used	NM105	1037	Name Middle Individual middle name or initial	O AN 1/25
Not Used	NM106	1038	Name Prefix Prefix to individual name	O AN 1/10
Not Used	NM107	1039	Name Suffix Suffix to individual name	O AN 1/10
	NM108	66	Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67) 1 D-U-N-S Number, Dun & Bradstreet 9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix 10 Department of Defense Activity Address Code (DODAAC) M4 Department of Defense Routing Identifier Code (RIC)	X ID 1/2

	NM109	67	Identification Code Code identifying a party or other code	X	AN 2/80
Not Used	NM110	706	Entity Relationship Code Code describing entity relationship	X	ID 2/2
Not Used	NM111	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual	O	ID 2/3

Segment:	TED Technical Error Description
Position:	070
Loop:	TED Optional
Level:	Detail
Usage:	Optional
Max Use:	1
Purpose:	To identify the error and, if feasible, the erroneous segment, or data element, or both
Syntax Notes:	
Semantic Notes:	
Comments:	1 If used, TED02 will contain a generic description of the data in error (e.g., part number, date, reference number, etc.).

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	TED01	647	Application Error Condition Code Code indicating application error condition <i>Use any code.</i> Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 1/3
	TED02	3	Free Form Message Free-form text	O AN 1/60
Not Used	TED03	721	Segment ID Code Code defining the segment ID of the data segment in error (See Appendix A - Number 77)	O ID 2/3
Not Used	TED04	719	Segment Position in Transaction Set The numerical count position of this data segment from the start of the transaction set: the transaction set header is count position 1	O N0 1/6
Not Used	TED05	722	Element Position in Segment This is used to indicate the relative position of a simple data element, or the relative position of a composite data structure with the relative position of the component within the composite data structure, in error; in the data segment the count starts with 1 for the simple data element or composite data structure immediately following the segment ID	O N0 1/2
Not Used	TED06	725	Data Element Reference Number Reference number used to locate the data element in the Data Element Dictionary	O N0 1/4
	TED07	724	Copy of Bad Data Element This is a copy of the data element in error	O AN 1/99
	TED08	961	Data Element New Content New data which has replaced erroneous data	O AN 1/99

Segment: **LM** **Code Source Information**
Position: 085
Loop: LM Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To transmit standard code list identification information
Syntax Notes:
Semantic Notes:
Comments: 1 LM02 identifies the applicable industry code list source information.

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
M	LM01	559	Agency Qualifier Code	M ID 2/2
			Code identifying the agency assigning the code values	
			DF Department of Defense (DoD)	
Not Used	LM02	822	Source Subqualifier	O AN 1/15
			A reference that indicates the table or text maintained by the Source Qualifier	

Segment: **LQ** Industry Code
Position: 086
Loop: LQ Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: Code to transmit standard industry codes
Syntax Notes: 1 If LQ01 is present, then LQ02 is required.
Semantic Notes:
Comments:

Data Element Summary

Ref.	Data		
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
LQ01	1270	Code List Qualifier Code	O ID 1/3
		Code identifying a specific industry code list	
		<i>Use any code.</i>	
		Refer to 004010 Data Element Dictionary for acceptable code values.	
LQ02	1271	Industry Code	X AN 1/30
		Code indicating a code from a specific industry code list	

Segment: **SE** Transaction Set Trailer
Position: 090
Loop:
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:**Semantic Notes:**

Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

	Ref.	Data		
	<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	SE01	96	Number of Included Segments	M N0 1/10
			Total number of segments included in a transaction set including ST and SE segments	
M	SE02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	
			<i>This is the number cited in ST02.</i>	